



470-479 DARK RANGE SMOOTH



PAWNEE PAVER

PAVER SIZES & SPECIFICATIONS

Pawnee Pavers are available in Standard size 2-1/4" thickness x 4" width x 8" length and also meet ASTM C 902-05 specifications. 470-479 Dark Range pavers are available in several sizes. 1-1/8" thick x 3-5/8" width x 7-5/8" length, smooth texture; 2-1/4" thick x 3-5/8" width x 7-5/8" length, smooth or wirecut texture; and 2-1/4" thick x 4" width x 8" length, smooth or wirecut texture. These brick also meet ASTM C 902-05 specifications.

For installation information and technical assistance on paving brick applications please refer to the Brick Industry Associations website at www.gobrick.com and click on the technical notes section. Technical Notes 14 and 14A will provide you with assistance in applications and materials. The Brick Industry also has literature on flexible brick paving titled "Pedestrian and Light Traffic Applications" and "A Heavy Duty Applications Guide" to assist you.

AN ISO 9001:2000 REGISTERED QUALITY MANAGEMENT SYSTEM – ISO is a series of quality assurance standards published by the International Organization for Standards to provide a worldwide set of quality system guidelines and requirements. ISO 9000 is the first consistent set of international standards available to evaluate a company's ability to provide a quality product. In 1994 The Belden Brick Company became the first U.S. brick manufacturer to obtain ISO 9001:2000 certification and maintains ISO 9001:2000 certification on a yearly basis.



BELDEN
CLAY PAVERS



BELDEN
THE BELDEN BRICK COMPANY



P.O. BOX 20910
CANTON, OHIO 44701-0910
PHONE: 330.456.0031
AN ISO 9001:2000 REGISTERED QUALITY MANAGEMENT SYSTEM
WWW.BELDENBRICK.COM

CITY LINE

City Line Pavers are manufactured with chamfered edges and spacer lugs. Other options are chamfered edge with no lugs, straight edge and straight edge with lugs. Two different size options are also available. Standard size 2-1/4" thick x 4" width x 8" length to meet ASTM C 902-05 pedestrian & light traffic paving brick specifications or Jumbo size 2-3/4" thick x 4" width x 8" length to meet ASTM C 1272-05, Type F, standard specification for heavy vehicular paving brick.



ADMIRAL RED



ADMIRAL FULL RANGE



CHESTNUT HILL CLEAR



CHESTNUT HILL FULL RANGE



CLARET



CLARET FULL RANGE



KODIAK BROWN



LANDMARK GRAY



LIGHTHOUSE GRAY



NUTMEG CLEAR



NUTMEG FULL RANGE



ONYX



REGIMENTAL FULL RANGE



REGIMENTAL MEDIUM RANGE



REGIMENTAL RED



TUMBLEWEED



WHEATFIELD

Due to printing limitations and lighting variations, the color may vary from the actual brick. We recommend viewing brick samples prior to selection. See your authorized Belden Brick dealer.

CITY LINE PAVERS ARE AVAILABLE IN CHAMFERED WITH LUGS, CHAMFERED EDGE, STRAIGHT EDGE WITH LUGS & STRAIGHT EDGE. 8" X 8" UNITS AND ADA COMPLIANT UNITS ALSO AVAILABLE.



CHAMFERED W/LUGS



CHAMFERED EDGE



STRAIGHT EDGE W/LUGS



STRAIGHT EDGE



4" x 4" PAVER



ADA PAVER



SANDMOLD PAVER

8" x 8" PAVERS



LANDMARK GRAY



WHEATFIELD



REGIMENTAL RED



CLARET

BELCREST



BELCREST 100



BELCREST 350



BELCREST 500



BELCREST 530



BELCREST 560



BELCREST 700



BELCREST 730



BELCREST 760

Our Belcrest line of paving brick is available in Modular size, 2-1/4" thick x 3-5/8" width x 7-5/8" length. These paving brick meet ASTM C 902-05 pedestrian and light traffic paving brick specifications.